Designing Smarter Structures:

From Topology Optimization to 3D Printing

Dr. Vagelis Plevris

Associate Professor, Department of Civil and Environmental Engineering, College of Engineering – Qatar University



Look carefully at a tree. Its trunk does not taper evenly from top to bottom; it thickens precisely where it needs to resist bending and splits into branches exactly where loads diverge. There is no wasted wood and no redundant material, only structure shaped by force. Now imagine applying that same principle to the beams, columns, and canopies of civil engineering. That is the promise of topology optimization, which formed the central focus of a recently completed research project at Qatar University.

In Qatar, where rapid infrastructure development meets a growing national commitment to sustainability, the question of how to build more with less material is not abstract. It is directly aligned with Qatar University's research priorities in Resource Sustainability and Digital Technology, and with Qatar's broader vision for efficient, innovation-driven development.

This idea is not only theoretical. The Qatar National Convention Centre, designed by the Japanese architect Arata Isozaki, is supported by a pair of enormous branching concrete columns inspired by the Sidra tree, Qatar's national symbol. The columns divide and subdivide in precisely the pattern that structural logic demands: widening where forces are greatest, branching where loads split. The result is a building that looks organic because it is structurally honest. What topology optimization does is take that same intuition and make it computational, applicable to every beam, frame, and canopy we design.

What Is Topology Optimization?

In conventional structural design, an engineer starts with a shape, such as a rectangular beam or a solid column, and checks whether it is strong enough. Topology optimization reverses this logic. Given a space, a set of loads, and a target for how much material to use, the algorithm decides for itself where that material should go. As a result, material gathers along the paths that carry force and vanishes from regions that do not contribute to structural performance. The

structures that emerge look organic, almost biological, because they are governed by the same mechanical logic that shapes bones and shells.

This approach is not new in aerospace engineering, where every gram saved translates directly to performance and cost. But its systematic application to civil engineering structures, with a clear connection to how those structures can actually be built, remains an open frontier.

The Project: From Simple Beams to a Parking Shade

The project, titled "Empowering Research in Structural Engineering through Topology Optimization and Additive Manufacturing: A Hands-On Approach", was funded by the Qatar National Research Fund through the Undergraduate Research Experience Program (UREP). It ran from January 2025 to January 2026 and involved six undergraduate students alongside academic mentors from the Department of Civil and Environmental Engineering.

The team investigated four structural systems of progressively increasing complexity: a cantilever beam, a simply supported beam, a parking canopy element subjected to combined forces and moments, and finally a full three-dimensional parking shade structure—a configuration directly relevant to Qatar's built environment.

For each structure, the team first established a reference design: a conventional solid geometry analyzed under realistic loading. Topology optimization was then applied, progressively reducing the amount of retained material from 70% down to 30% of the original volume, while tracking how structural performance responded to each reduction.

The Results: How Much Can You Remove?

The results were consistent and revealing across all cases. Material reductions of 40–50% were achievable without compromising structural safety or exceeding acceptable deformation limits. The algorithm reliably identified which parts of the structure were doing real work and which were not.

But the relationship between material reduction and structural performance is not linear. Moderate reductions (removing 30 to 40% of material) yield the most attractive trade-off: meaningful savings




Figure 1: Topology optimization results for a 3D parking shade structure. At 60% retained mass (left) and 50% (right), material concentrates along dominant load-carrying paths while low-stress regions are hollowed out, producing organic, tree-like column forms.

with modest increases in stress and deflection. Push the reduction further, and the structure begins to strain. Safety margins narrow sharply, and deformations climb. The message from the data is clear: there is a sweet spot, and finding it requires careful analysis rather than aggressive optimization.




Figure 2: Structural performance of the parking shade structure at different levels of material reduction. As retained mass decreases from 100% to 50%, stress increases, displacement grows, and the factor of safety (FoS) drops, illustrating the trade-off that must be managed in practice.

From Screen to Object: The Role of 3D Printing

Topology-optimized geometries are often impossible to build using conventional fabrication methods. A structure shaped by load paths rather than straight lines cannot easily be cast in a mold or cut from a sheet. This is where additive manufacturing becomes essential. It imposes no geometric constraints: any form the algorithm generates can be printed, layer by layer, exactly as designed.

The team fabricated both the conventional and optimized versions of selected structures using polymer-based 3D printing. The physical models make the difference immediately visible in a way that no chart can: one version is blocky and uniform; the other is hollowed out and branching, carrying the same load with a fraction of the material.




Figure 3: Physical prototypes produced by 3D printing. Left: the beam, showing the solid baseline (bottom) compared with the lightweight optimized design (top). Right: the parking shade structure: conventional solid design (white) beside the topology-optimized version (blue), with its characteristic branching column form.

To confirm that the results were not artifacts of a single software platform, the team ran parallel implementations: Autodesk Fusion 360 for commercial optimization, and custom MATLAB code for an independent algorithmic check. The two approaches agreed closely.

Learning by Doing: The UREP Experience

The UREP program is built on a straightforward but powerful idea: undergraduate students learn research by doing research. Over twelve months, the six students moved through the complete arc of a research investigation, from building computational models and running simulations to writing code and producing a physical object they had designed, optimized, and 3D-printed.

That last step—holding the object—matters more than it might seem. Abstract concepts like load paths and factors of safety become tangible when you can compare two printed structures that look radically different but carry the same load. The students developed proficiency in professional CAD and finite element software, in programming and algorithm implementation, and in the practical realities of digital fabrication. They also learned how to work as a team, interpret data, and communicate technical findings, skills that will serve them well beyond any single project.

A New Way of Thinking About Structure

Topology optimization and additive manufacturing are not futuristic technologies; they are already available today. Qatar's infrastructure ambitions are large, and so is the opportunity to embed efficiency and sustainability into how structures are conceived from the outset. This project is a modest but concrete step in that direction, and it provides evidence that the next generation of engineers at Qatar University is already learning to build not just stronger structures, but smarter ones.

Acknowledgment

This project (UREP31043-2-139-) was made possible by a UREP award from the Qatar National Research Fund (QNRF), a member of Qatar Foundation. The findings are the sole responsibility of the authors.

